


PITO™ Greenline lifeline system








The PITO™ Greenline lifeline system allows for safe and easy movement when working on the roof. A person connected to the lifeline is protected for the entire length of the line, and there is no need to disconnect from the line at the anchor points.

- Up to four users at the same time.
- Installed between PITO™ roof anchor posts and anchor points.
- Installation must be carried out only by Peltitarvike's own authorized installers.
- Span of the cable up to 15 m, depending on the type of anchor point, recommendation 7,5-10 m or 10-12 m.
- Maximum length of the cable line depends on the type of anchor point, 150 or 250 m.
- CE marked.
- Tested according to the fall protection equipment standards EN 795:2012 Type A + C and CEN/TS 16415:2013 Type A + C.







PITO™ Variant K roof anchor point

- Available in black-powder-coated steel. The bottom can be drilled with the roof anchor post.
- Span length of cable 150 m or 250 m.





PITO™ Clip 2 anchor point

- Available in black-powder-coated steel. The double-clamping system must be continuously for a minimum of 100 mm in both directions measured from the middle of the anchor point.
- May not be drilled with the anchor post or hole.
- Adjustable in maximum 30° angle.
- Maximum distance between adjacent anchor points is 10 m in 100°-180° system, maximum distance is 12 m in 90° corner system and 15 m in other anchor points.







PITO™ Clip 1 anchor point

- Only for use in connection with cable points for 100° systems.
- Available in double-clamping system version. The double-clamping system must not be continuously for a minimum of 100 mm in both directions measured from the middle of the anchor point.
- May not be drilled with the anchor post or hole.
- Adjustable in maximum 30° angle.
- Maximum distance between adjacent anchor points is 10 m in 100°-180° system, maximum distance is 12 m in 90° corner system and 15 m in other anchor points.










PITO™ Variant Uni roof anchor point

- Available in 100° system, 180° and in mounting in a corner roof. The bottom can be drilled with the roof anchor post.
- 100° system: maximum 10 m.
- 180° system: maximum 10 m.
- Mounting in a corner: 15 m.
- Span length of cable 150 m or 250 m.
- The cable length of cable is up to 100 m.









PITO™ roof anchor post

- Available in 100° system, 180° and in mounting in a corner roof. The bottom can be drilled with the roof anchor post.
- Span length of cable 150 m or 250 m.






PITO™ cast-in anchor post

- Available in 100° system, 180° and in mounting in a corner roof. The bottom can be drilled with the roof anchor post.
- Span length of cable 150 m or 250 m.



PITO™ anchor rod, wall anchor point

- Available in 100° system, 180° and in mounting in a corner roof. The bottom can be drilled with the roof anchor post.
- Span length of cable 150 m or 250 m.



PITO™ Stonekit counterweight anchor point

- Available in 100° system, 180° and in mounting in a corner roof. The bottom can be drilled with the roof anchor post.
- Span length of cable 150 m or 250 m.

